

Technisches Datenblatt

Glass fiber mesh 03-8; 03-8/110

Product description

Fibreglass mesh fabric for facade insulation;

Application

Reinforcing mesh for External Thermal Insulation Composite System

Technical properties

Area mass (impregnated)	205 g/m ² ± 5 %	
Ash content	(84 ± 4) %	
Organic content	(16 ± 4) %	
Tensile strength	In state of delivery:	After aging (ETAG004):
Warp direction	≥ 38 N/mm	≥ 50% und ≥ 22 N/mm
Weft direction	≥ 38 N/mm	≥ 50% und ≥ 22 N/mm
Elongation at break	In state of delivery:	After aging (ETAG004):
Warp direction	≤ 5,5 %	≤ 3,5 %
Weft direction	≤ 5,5 %	≤ 3,5 %
Heat of combustion	5,25 MJ/kg	

Dimensions

Mesh opening	
Warp direction	(5,5 ± 0,5) mm
Weft direction	(6,0 ± 0,5) mm
Average Meshsize	
Warp direction	(7,0 ± 0,5) mm
Weft direction	(6,5 ± 0,5) mm
Mesh width	1.000 mm ± 1 % / 1.100 mm ± 1 %
Mesh thickness	(0,8 ± 0,2) mm
Weaving accuracy	pass